



# CigaretteBuster™

## Air Vent Mount – Model 79xx

### Technical Specifications



Model	Power Source	Output Type	External Output Device	Output Range
7910	4 AA Batteries	Long range wireless	RF Receiver to pager	Receiver: up to 1000' Pager: 1.5 miles
7920	4 AA Batteries	Local (internal) alarm	None	In room
7930	4 AA Batteries	Short range wireless	Horn and/or Strobe	20' to 50'
7940	12 volt DC	Wired relay	Horn and/or Strobe	5000'
7950	12 volt DC	Local (internal) alarm and wired relay	Horn and/or Strobe	In room and 5000'
7978	Two 9V Batteries	Local (internal) voice message	None	In Room

## Specifications

### Performance:

- Coverage: 360 degree Line Of Sight (LOS); 200 sq ft
- Battery life: approximately 1 year
- Delay options: 0 or 30 seconds (standard except 7910)
- Latch time options: 3 or 30 seconds (standard; wired and local only)
- Alarm volume: 90 dB

### Electrical:

- Four AA batteries  
(Two 9V for model 7978)
- 12 volt DC, 4.7 ma draw
- Relay contact rating 3A
- Open collector output

### Physical:

- Width 7.5" (20 cm)
- Length 13.25" (34 cm)
- Height 2.75" (7 cm) above vent
- Weight 20 oz (0.6 kg)
- Installation 2 screws

Questions, comments, or concerns:

#### **Voice Products, LLC**

23715 Mercantile Road #200, Cleveland OH 44122 USA

phone: 216-360-0433 • fax: 216-360-9805

email: [sales@cigarettesmokedetector.com](mailto:sales@cigarettesmokedetector.com)

web: [www.cigarettesmokedetector.com](http://www.cigarettesmokedetector.com)

US Patent 6,545,608

*The world leader in smoking rules enforcement!*